

O Series  
**TOOLS**

---



# TOOLS

O-1



O	5 mm
L	160 mm
A	33 mm
kg/Pc	0.025
Pc/Ctn	396

O-2



O	5 mm
L1	123 mm
L2	16 mm
kg/Pc	0.103
Pc/Ctn	20

O-3/O-3A



Cutting Range	3-32 mm
Set	1 X O-3
Optional Parts	2 X O-3A
kg/Pc	0.417 / 0.019
Pc/Ctn	12

O-4



Cutting Range	Φ 6 - Φ 40 mm
kg/Pc	0.230
Pc/Ctn	32
Tube inside and outside trimming knife.	

O-5/O-5A



Packaging (included)	1xO-5 ordinary trimming blade
	1xO-5A high strength trimming blade
kg/Pc	0.060 / 0.021

O-6



O	13 / 16 mm
Thicknes	3.2 mm
kg/Pc	0.050
Pc/Ctn	200
For caster assembling.	

O-7



L1	1800 mm
L2 Range	0-1800 mm

O-8



Sawing Range (mm)	○	Φ 95
	□	85 X 85
		110 X 75
	●	Φ 55
Max Clamp	■	50 X 50
		110 mm
Main Motor		4/2 1.8 / 2.4 KW
Saw Blade Type		250 / 275 / 300